Protection like no Other.

Bodyguard.

Bodyguard. is pre-primed (double coated) and the following are recommended for optimum performance:

- Bodyguard products must be painted as soon as practicable after installation.
- Bodyguard products must be dry before commencing painting (a moisture content of 14% or less).
- Apply top coat in warm, dry weather not below 50° F.
- Painting with solid acrylic stains is not recommended as UV light will penetrate the transparent stain and damage the primer paint.
- · We recommend application of the first top coat prior to installation.
- 1. Nail holes: if nails are countersunk. seal exposed wood with Bodyguard End Seal then fill nail holes with an exterior grade wood filler, then spot prime. In temperatures less than 40°F use cold weather caulking sealants.
- 2. Remove all soft and chalky paint, dirt,
- 3. Apply two full coats of premium quality exterior acrylic house paint as per manufacturer's instructions. For best results allow 24hrs between
- 4. The use of colors with a Light Reflectance Value (LRV) of 45 or more is recommended, as these lighter colors reflect significantly more heat.
- 5. When cutting or re-machining: brush or spray-on a preservative containing zinc naphthenate, Bodyguard End Seal is recommended.
- 6. Corrosion resistant fasteners such as hot dipped galvanized nails or stainless steel nails must be used when installing.
- 7. All nails should be countersunk and puttied prior to paint.



For more options, please see our website ELandELWoodProducts.com

©2023 Metrie EL & EL, LLC.

23012401.10m.05.18

Attention California Residents. Proposition 65 Warning:

as a chemical known to cause cancer in humans. Wood dust can also cause a flammable or explosive hazard. Sawing, sanding.

- · Avoid dust contact with an ignition source.
- · Avoid prolonged breathing of wood dust and contact with the eyes and skin.







801BG T&G Reverse Side Shown


372 Rab't Siding - 3/4"x 8"



The State of California (OEHHA Prop 65) has classified wood dust and machining wood products can produce wood dust.



· Recover dust for disposal.



Non-Corrosive

Pressure Treated

and sand etc. to a smooth even finish.

Protected Trimboard & Siding

Protected Trimboard

Sutable for Interior / Exterior Use Available in 16' & 20' lengths*
Reversible

Rough-Sawn on one (1) Side, Smooth on the other three (3), with Eased Edges.







Part No.	SIZE (Actual)
5/4X4S1S*	5/4"x 4" (1" x 3½")
5/4X6S1S*	5/4"x 6" (1" x 5½")
5/4X8S1S*	5/4"x 8" (1" x 7 ¹ / ₄ ")
'	*Available in 16' Only



Part No.	SIZE (Actual)
2X2S1S	2"x 2" (1½" x 1½")
2X4S1S	2"x 4" (1½" x 3½")
2X6S1S	2"x 6" (1½" x 5½")
2X8S1S	2"x 8" (1½" x 7½")
2X10S1S	2"x 10" (1½" x 9½")
2X12S1S	2"x 12" (1½" x 11½")

Protected Beaded T&G

Suitable for Interior / Exterior Use Available in 16' lengths

CalFire Rated Non-Reversible



Part No.	SIZE	Face Exposed
801BG*	5/8" x 4"	3-1/8"
802BG*	1" x 6"	5-1/8"

*Available in 16' Only

Protected Siding

1X12S1S

Available in 16' & 20' lengths* CalFire Rated[†]



1"x 12" (3/4" x 111/4")

Rab't Siding (Smooth Face Rough Sawn Back) SIZE (Actual)

371	3/4"x 6"	(11/16" x 5-1/2")
372	3/4"x 8"	(11/16" x 7-1/2")
373	3/4"x 10"	(11/16" x 9-1/2")



V-Rustic Siding

Part No.	SIZE (Actual)
793	1"x 6" (3/4" x 5-1/2") 1"x 8" (3/4" x 7-1/2") 1"x 10" (3/4" x 9-1/2")
794	1"x 8" (3/4" x 7-1/2")
795	1"x 10" (3/4" x 9-1/2")



Cove Siding

Part No.	SIZE (Actual)
771 [*]	1"x 8" (3/4" x 7-1/2")
772	1"x 10" (3/4" x 9-1/2")
	*Available in 16! Only



Lap Siding

_		
	Part No.	SIZE (Actual)
Т	430	1"x 6" (3/4" x 5-1/2")
	432	1"x 8" (3/4" x 7-1/2")
	433	1"x 10" (3/4" x 9-1/2")



Bevel Channel Siding

Part No.	SIZE (Actual)	
774	1"x 8" (3/4" x 7-1/2")	
773	1"x 10" (3/4" x 9-1/2")	



Bevel Siding (#400)

Part No.	SIZE (Actual)
1X4BS [†]	1/2"x 4" (1/2" x 4")
	†Not CalFire Bated



Double Nickel Gap Siding

Part No.	SIZE (Actual)
1X6NGS [†]	1"x 6" (6/8" x 5-1/2")

†Not CalFire Rated



